

## PRODUCT INFORMATION AND SPECIFICATION SHEET

**Product name :** HX STANDARD DUTY KELIFLEX SUCTION & DELIVERY HOSE


**Description :** Spirally reinforced standard duty PVC suction hose. 30M lengths available in transparent yellow with white rigid.

**Application :** Suction and delivery of liquids and mixtures in sewage transfer, agriculture, mining, industrial, civils, fishing, dredging, etc.

**Advantages :** Flexible, UV stabilized smooth bore, full flow.  
 Abrasion, shock and crush resistant.  
 Temperature ranges 0 - 60 Celsius.  
 Non toxic PVC.  
 Can withstand vacuum.  
 PROUDLY MADE IN SOUTH AFRICA.

**Specifications :** HX STANDARD DUTY KELIFLEX SUCTION & DELIVERY HOSE

ID (mm)	ID (inches)	Bursting pressure (bar)	Bend radius (mm)	Weight (Kg/M)	Weight per roll
25.4mm	1"	24	110	0.38	11.4
31.75mm	1 1/4"	21	130	0.48	14.4
38.1mm	1.5"	18	155	0.6	18
50.8mm	2"	15	215	0.85	25.5
63.5mm	2.5"	14	275	1.05	31.5
76.2mm	3"	12	335	1.5	45
101.6mm	4"	11	450	2.6	78



**Disclaimer :** The specifications listed are a guideline only, and the information provided may vary from time to time. All measurements indicated above are target spec, tolerance levels are within factory spec. We reserve the unconditional right to change the specifications, and will not be held liable for any loss, injury or damage whatsoever